REF-UR-1220-04

Commercial 4 Solid Door Upright Fridge, 1220x760 x 1980mm High



1220 x 760 x 1980
W X D X H (MM)

689L
NET VOLUME

+2 to +8 deg C
TEMPERATURE RANGE

10A single phase
POWER

OVERVIEW

A tropical-rated upright stainless fridge with 4 half doors. It holds +2 to +8 deg C over four shelf levels plus the floor, and the doors self-close and lock. Highlights: Doors Close Themselves And Lock; Digital Temperature Controller With Readout; Fan-Forced Evaporator; Automatic Defrost; Drains By Self-Evaporation; Insulation Free Of CFCs And HCFCs.

FULL SPECIFICATIONS

Dimensions (W x D x H)	1220 x 760 x 1980mm
Temperature Range	+2 to +8 deg C
Net Volume	689L
Gross Volume	1000L
Doors	4 half doors, solid
Shelving	4 levels plus floor
Cooling System	Fan forced
Defrost	Automatic
Energy Rating	2 Star GEMS
Food Safety	4M1 certified
Body	Stainless steel inside and out
Mobility	Castors
Power	10A single phase (706W)
Warranty	2 Years Parts & Labour + 2 Years Parts Only with product registration within 14 days of invoice