REF-UR-1340-03

Commercial 4 Solid Door Upright Fridge, 791L, 1340x840 x 2000mm High



1340 x 840 x 2000
W X D X H (MM)

791L
NET VOLUME

-2 to +8°C
TEMPERATURE RANGE

10A single phase
POWER

OVERVIEW

A tropicalised upright stainless fridge with 4 split half doors. It holds -2 to +8°C on three shelf levels and is rated for 43°C kitchens.

HIGHLIGHTS

- Split Half Doors For Faster Recovery And Lower Running Costs
- Shelves Take 2 x GN 1/1 Pans
- Tropicalised For Australian Conditions
- Self-Closing Lockable Doors, Heavy-Duty Magnetic Seals
- Door Handle Set Into The Door, Easy To Wipe
- Evaporator And Condenser Fans Built For Heavy Use

FULL SPECIFICATIONS

Dimensions (W x D x H)	1340 x 840 x 2000mm
Temperature Range	-2 to +8°C
Net Volume	791L
Gross Volume	1236L
Internal Size	1224mm (W) x 682mm (D) x 1394mm (H)
Doors	4 split half doors, solid
Shelving	3 levels plus base, 40kg per shelf
Cooling System	Fan forced
Max Ambient	43°C / 60% RH
Refrigerant	R290
Defrost	Automatic
Energy Rating	3 Star GEMS
Food Safety	4M1 certified
Body	Stainless steel
Mobility	Heavy-duty castors, front brakes
Power	10A single phase (430W)
Warranty	2 Years Parts & Labour + 2 Years Parts Only with product registration within 14 days of invoice